

Perforated Tubing Design Kit

Contact Information	
Company	
Contact Name	
Phone	
Email	
Street	
City	
State	
Zip	
Project Specifications	
<p>The diagram illustrates the design of a perforated tube. It shows two side views: a 'Straight Pattern' and a 'Staggered Pattern'. The 'Straight Pattern' shows a grid of holes with a 'C - Margin' on the left and 'C' on the right. The 'Staggered Pattern' shows a grid of holes where the holes in adjacent rows are offset. Dimensions are labeled: 'B Length' for the total length, 'A OD' for the outside diameter, and 'D - Hole Centers' for the distance between hole centers. A circular cross-section of the tube is also shown to the right.</p>	
Part Number / Description	
Quantity	
Outside Diameter (A)	
Length (B)	
Margins (C), if required.	
Material Type	<input type="checkbox"/> HR <input type="checkbox"/> CRS <input type="checkbox"/> Stainless 304 <input type="checkbox"/> Stainless 409 <input type="checkbox"/> Stainless 316 <input type="checkbox"/> Stainless316 L <input type="checkbox"/> Other

BEVERLIN

MANUFACTURING CORPORATION
CUSTOM PERFORATED TUBING

3515 Raleigh Ave SE
 Grand Rapids, Michigan
 49512-2041, US
 Phone: (616) 949.5990
 Fax: (616) 949.0873
 www.beverlin.com

Material Thickness	<input type="checkbox"/> 28 Ga. (0.0149) <input type="checkbox"/> 26 Ga. (0.0179) <input type="checkbox"/> 25 Ga. (0.0209) <input type="checkbox"/> 24 Ga. (0.0239) <input type="checkbox"/> 22 Ga. (0.0299) <input type="checkbox"/> 20 Ga. (0.0359) <input type="checkbox"/> 19 Ga. (0.0418)	<input type="checkbox"/> 18 Ga. (0.0478) <input type="checkbox"/> 16 Ga. (0.0598) <input type="checkbox"/> 14 Ga. (0.0747) <input type="checkbox"/> 13 Ga. (0.0897) <input type="checkbox"/> 12 Ga. (0.1046) <input type="checkbox"/> 11 Ga. (0.1196) <input type="checkbox"/> Other
Hole Diameter		
Hole Centers (D)		
Hole Pattern	<input type="checkbox"/> Staggered <input type="checkbox"/> Straight <input type="checkbox"/> Other	
% Open area		
Seam Style	<input type="checkbox"/> Straight Weld <input type="checkbox"/> Spiral Weld <input type="checkbox"/> Straight Tack Weld	<input type="checkbox"/> Straight Overlap Spot Weld <input type="checkbox"/> Straight Lock seam
Finish	<input type="checkbox"/> None <input type="checkbox"/> Lightly Oiled <input type="checkbox"/> Zinc <input type="checkbox"/> Zinc Dichromate <input type="checkbox"/> Chrome	<input type="checkbox"/> Nickel <input type="checkbox"/> Paint <input type="checkbox"/> Powder-coat <input type="checkbox"/> Other
Perforation Burrs		
Special Requirements		
Special Assemblies		
Application		

After completing this form please fax it to Beverlin Manufacturing at

(616) 949.0873

or mail it to us at

**Beverlin Manufacturing Corporation
 3515 Raleigh Ave SE
 Grand Rapids, Michigan
 49512-2041, US**

Thank you for your time and we will be contacting you ASAP.

Be sure to visit our website at www.beverlin.com